

WRXK1S Mini One-Step Cleaver

Stable, Small and Lightweight

The WRXK1S mini one-step precision cleaver with waste bin offers high precision fiber cleaving for 250um, 900um, 2mm, 3mm single fiber and ribbon cable. Small in size, it has a footprint of 3" x 3" and weighs only 5 ounces. Simple one-step operation maximizes work efficiency and provides a consistent cleave angle of 90 +/- 0.5 degrees. Blade automatically resets to the start position. Steel blade is made of high hardness tungsten steel and comes with 24 blade positions. Blade rotation is made easy with a simple slide button and it also includes an easy access screw for adjusting blade height.



Features

- One-step precision cleaver with automatic blade reset
- Small and lightweight handheld precision cleaver with bin
- Stable operation with 90 +/- 0.5 degree cleave angle
- Cleaves 250um, 900um, 2mm, 3mm cable and ribbon cable
- Compatible with industry standard fiber holders
- High hardness tungsten steel blade with 24 blade positions
- Slide button offers easy blade rotation



Specifications

Parameter	Value
Applicable Fiber	250um, 900um, 2mm, 3mm, ribbon cable up to 12 fibers.
Fiber Cleave Length	9mm - 16mm
Fiber Cleave Angle	90 degrees +/- 0.5 degrees
Holder	Universal fiber adapter plate
Weight/Dimensions	5 ounces / 3"(L) x 3" (W) x 1" (H)

Ordering Information

Part Number	Description
WRXK1S-M	Mini one-step handheld precision cleaver with bin includes plastic hard case